

## 8026DN/DTN Colour Laser Printer

Bring colour to your business with TallyGenicom's top of the range Network Colour Laser Printer



- Fast 26 ppm Colour, 35 ppm Mono
- PCL5/6 and Adobe PostScript standard
- Robust monthly workload up to 90,000 pages per month
- Ethernet, USB2 and Parallel standard
- Intellifilter forms management
- 1200 dpi for quality business documents
- Duplex standard
- Prints on a variety of media including plain paper, transparencies, thick paper, labels, banner and envelopes

### **Meet the demands of the busy office with the 8026DN/DTN**

TallyGenicom's fastest to date colour laser printer exceeds all your expectations with its high speed. The 8026DN/DTN delivers 26 ppm in full colour and 35ppm in black and white, increasing the efficiency in your workplace.

TallyGenicom Intelliprint technology ensures professional high quality colour output, text graphics, reports, presentations, even photographs, all in bright vibrant colours.

All this speed and quality is backed up by an extremely robust engine and guaranteed reliability you expect from TallyGenicom.

The 8026DN/DTN boasts an impressive list of paper handling features, a maximum paper capacity of 2350 sheets is achievable, more than enough for any office. Fuss free remote management with TallyGenicom's embedded Webserver is simple to use together with installation utilities, maximises your productivity.

---

Available Configuration:

**8026DN** Standard Product (with Duplex)  
**8026DTN** with Duplex and additional tray

- Print Speed** Colour: Up to 26 pages per minute (letter), Mono: Up to 35 pages per minute (letter)
- Processor** MIPS R7000 533 Mhz
- Resolution** True 1200 dpi engine resolution
- Time To 1st Page** 6 seconds mono, 8 seconds colour. Engine print time will vary with page complexity
- Memory** 128MB expandable to 256MB (1 slot)
- Standard Connectivity** USB 2, Ethernet TCP/IP, (10BaseT/100BaseT), IEEE Parallel
- Optional Connectivity** Serial RS232 (Projects only)
- Standard Emulation** PCL5C, PCL6, Adobe PostScript 3
- Fonts** 80 PCL Fonts and 136 PostScript fonts
- Consumables** CMY=8,000 images each; K=9,000 images (based on A4 page @ 5% coverage); OPC < 35K pages; Bias Transfer roller < 35K; Fuser < 100K; Retard roll < 100K (Initial toners supplied are up to half life)
- STD Paper Handling** 8026DN: 150 sheet multi-purpose feeder and 550 sheet feeder; 8026DTN: 150 sheet multi-purpose feeder and 2 x 550 sheet feeders. Output: 250 sheet face down tray
- Opt'l Paper Handling** 1 x 550 sheet feeder, 2 x 550 sheet feeder (both can be installed)
- Duplexing** Auto Duplex standard
- Paper Type** Plain paper, transparencies, labels, heavy paper stock, banner, envelopes, postcard and coated
- Paper Weight** Multi-purpose: 60-216gsm. 550 ASF: 60-163gsm. Duplex: 60-162gsm. Banner: 80-105gsm
- Paper Size** Multi-purpose: min 88.9x139.7mm, max 215.9x355.9mm. Banner: 355-900mm. 550 ASF: Letter, A4, A5, B5, Executive, Legal. Duplex: min 149x205mm, max 215.9x355.6mm
- Printable Area** Top, left, right, bottom - 4mm
- Physical Weight** 8026DN 34.5Kg inc. consumables; 8026DNT 56Kg inc. consumables
- PhysicalSize** 8026DN 429(w) x 580(d) x 457(h) mm. 8026DNT 429(w) x 590(d) x 798(h) mm
- Power Voltage** 580 Watts average operation; 1,300 Watts maximum
- Power Consumption** 45 Watts in sleep mode (fuser off), 200 Watts in standby (fuser on)
- Compliance** Energy Star Compliant
- Workload** Up to 90,000 pages per month max., 10,000-17,000 pages per month av., Engine Life - 600,000 pages
- Reliability MTBF** 100,000 pages
- Reliability MTTR** Less than 30 minutes
- Drivers** Windows® XP/2003/2000/ME/98se/MAC OS X.x & 9/Linux via PPD
- Temperature** 5° - 32°C
- Humidity** 15% - 85% relative humidity, non-condensing
- Acoustic** Operating - less than 55dB(A), standby - less than 35dB(A), sleep - background. Sound power. Operating - 6.65 B, standby - 5.0 B, sleep - background
- Warranty** 2 years on site next business day
- Note** Exceeding the monthly duty cycle will not void the warranty if TG consumables and maintenance kits are used.

Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice. Copyright © 2007 TallyGenicom, L.P.

Printed Date: 22/09/2007



Rutherford Road, Basingstoke,  
Hampshire RG24 8PD  
Tel: UK 0800 652 4557  
International: +44 1256 481 521  
Fax: UK 0870 872 2889  
www.tallygenicom.co.uk