

TallyGenicom 6600 Series of Line Matrix Printers

Technical Specifications

the Power
of



Printer Features		Open Pedestal	6605 6610 6615	Quiet Pedestal	6605 6610 6615	Zero Tear	6605Z 6610Z 6615Z	Cabinet	6605Q 6610Q 6615Q	6620Q
Standard										
Integrated Print Management		●		●		●		●		
Ribbon Life Monitor		●		●		●		●		
Options										
SureStak® Power Stacker								●		
Black back forms paper out sensor		●		●		●		●		
Rear Slide Out Paper Drawer								●		
Cabinet Front Access								●		
Pedestal Front Paper Tray		●				●				
Pedestal High Rear Paper Tray		●		●		●				
Pedestal Acoustic Shroud		●		Standard						
Physical Size	Height	36”(914.4mm)		36”(914.4mm)		42”(1066.8mm)		40.5”(128.7mm)		40.5”(1028.7mm)
	Width	26”(660.4mm)		26”(660.4mm)		26”(660.4mm)		27”(685.8mm)		27”(685.8mm)
	Depth	21.5”(546.1mm)		25”(635mm)		21.5”(546.1mm)		29”(736.6mm)		33”(838mm)
	Shipping Weight	165 lbs (74.842kg)		190 lbs (86.182kg)		180 lbs (81.646kg)		265 lbs (120.201kg)		300 lbs (136kg)
		Not including rear tray		With acoustic shroud						With SureStak Power Stacker
Acoustic (dBA) (per ISO 7779)		6605 - 62		6605 - 58		6605Z - 66		6605Q - 50		
		6610 - 65		6610 - 60		6610Z - 70		6610Q - 50		
		6615 - 68		6615 - 63		6615Z - 70		6615Q - 52		6620Q - 55
		6605 6605Q 6605Z		6610 6610Q 6610Z		6615 6615Q 6615Z		6620Q		
shown by Printer models										
Print Speed (LPM, upper case characters, lower case characters)	High Speed (draft)	500/428		1000/856		1500/1289		2000/1700		
	Data Processing	375/300		750/600		1125/900		1500/1200		
	Near Letter Quality	200/154		400/306		600/459		800/615		
Graphics Speed (Inches Per Minute)	60 x 48 dpi	63		125		187		250		
	60 x 72 dpi	42		83		127		167		
	90 x 96 dpi	21		42		61		83		
Paper Feed Speed (Inches Per Second)		12		20		25		38.5		



tg TallyGenicom®
BY PRINTRONIX

TallyGenicom 6600 Family of Line Matrix Printers

Character Pitch	5, 6, 6.7, 7.5, 8.3, 8.6, 10, 12, 13.3, 15, 16.7, 17.1, 20 (characters per inch)			
Line Spacing	1.5, 2, 3, 4, 5, 6, 8, 9, 10, 12 (lines per inch – plus variable line spacing)			
Graphics Resolution	240 dpi Horizontal, 288 dpi Vertical (max)			
Dot Size	16.7 mil (.42mm)			
Emulations Standard	Tally ANSI, Genicom ANSI, P5000/P600/P6000, Epson FX-1180, IBM Proprinter, MTPL (Tally Dot Matrix), PGL (TG Version), QMS Code V, Tally Industrial Graphics, PCL-3: HP-2564C, DEC LG01			
Character Sets	47 languages and 43 character sets			
Character Styles	Bold, italic, superscript, subscript, underline, overline, strike-through			
Fonts	Draft, Data Processing, Courier, Gothic, OCR A and B			
Barcodes	Code 39, Code 128, Interleaved 2 of 5, UPC-A, UPC-E, EAN 8, EAN 13, EAN 128, Codabar, MSI, PDF-417, Postnet, Intelligent Mail Barcode (IMB)			
Printer Software	TallyGenicom PrintNet Suite of Tools - remote management software suite - included with the Ethernet option			
Printer Drivers	Win 7, Vista, XP, Windows 2000, Server 2003, Server 2008, Server 2008r2, Linux, Unix, AIX, SAP			
Environmental Advantages	ENERGY STAR® qualified, lower consumable materials and packaging, improved handling of recycled paper, faster power-up from sleep mode than laser printers			
Genuine TallyGenicom Cartridge Ribbons	Standard Life	17,000 pages	*Not compatible with 500 LPM printer models	
	Extended Life*	30,000 pages		
Paper Path/Handling	Straight paper path with easy-load adjustable tractors, paper-out detection and alarm, paper-motion detection and alarm			
Paper Type	Continuous, fan folded, edge-perforation			
Print Width	13.6” (345mm)			
Media Width	3” (76mm) to 17” (432mm)			
Media Copies	Up to 6 parts			
Media Weight	15 to 100 lbs up to 0.025” thickness 56 to 163 gm/m² up to 0.64mm thickness			
MTBF*	10,000 hours at 25% duty cycle and 25% page density (*Mean Time Between Failures)			
Interfaces	Serial – RS-232 Parallel – IEEE-1284/Centronics Ethernet – PrintNet Suite 10/100 Base T (optional) Auto Switching – Between active ports			
Power Voltage	AC input range 88-270 VAC, 45 to 65 HZ			
Power Wattage (ENERGY STAR)	Less than 14 Watts in energy saving mode			
Power Wattage (typical)	6605/6605Q/6605Z 6610/6610Q/6610Z	175 Watts 260 Watts	6615/6615Q/6615Z 6620Q	390 Watts 475 Watts



© 2011 Printronix, Inc. All rights reserved. Genicom, Tally, TallyGenicom, TG TallyGenicom, the TG Logo, Intellifilter, Intelliprint, PrintNet Suite, PrintNet Enterprise, PrintNet, Smart Ribbon and Printronix are trademarks or registered trademarks of Printronix, Inc. All other trademarks, product names, company names or logos herein are the property of their respective owners. Product appearance and/or specifications are subject to change without notice.
Printed in USA. PTX_602A(4/11)



14600 Myford Road, Irvine, CA 92606
1-800-665-6210 • www.tallygenicom.com